

MARTIN WISMAN TPU 3250 - 100V pojačalo

MARTIN WISMAN TPU 3250 - 100V pojačalo

Šifra: 8132

Kategorija proizvoda: 100V pojačala

Proizvođač: Martin Wisman

Cena: **369,00** EUR

TPU 3250 - PA Amplifier, 250W

Features

Fan-cooled

3 Mic and 3 Aux inputs

70 V, 100 V PA-outputs

1 Mic-connection on the front panel, Chime button

Treble and bass control

Master-control

Protection-circuits: over current,

Screw terminals of 6 zone outputs

Specifications

| MODEL | TPU-3060 | TPU-3120 | TPU-3180 Z6 | TPU-3250 | TPU-3250 |
|--------------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|
| Power supply | AC110V~ 60 Hz | AC110V~ 60 Hz | AC110V~ 60 Hz | AC110V~ 60 Hz | AC110V~ 60 Hz |
| Output power | 60W RMS | 120W RMS | 180 W RMS | 250 W RMS | 350 W RMS |
| Output type | 70 V, 100 V or 4-16 | 70 V, 100 V or 4-16 | 70 V, 100 V or 4-16 | 70 V, 100 V or 4-16 | 70 V, 100 V or 4-16 |
| Output current at 70V | 0.9A | 1.4A | 2.5 A | 3.6 A | 5.0A |
| Output current at 100 V | 0.6A | 1.0A | 1.8 A | 2.5 A | 3.5A |
| Mic input | 5 mV, 600 Ohms | 5 mV, 600 Ohms | 5 mV, 600 Ohms | 5 mV, 600 Ohms | 5 mV, 600 Ohms |
| Line input | 300 mV, 10 kOhms | 300 mV, 10 kOhms | 300 mV, 10 kOhms | 300 mV, 10 kOhms | 300 mV, 10 kOhms |
| Frequency range | 80 Hz - 16 kHz | 80 Hz - 16 kHz | 80 Hz - 16 kHz | 80 Hz - 16 kHz | 80 Hz - 16 kHz |
| Distortion | 0.5 % (1 kHz) | 0.5 % (1 kHz) | 0.5 % (1 kHz) | 0.5 % (1 kHz) 0.5 | 0.5 % (1 kHz) |
| Signal/Noise ratio: | Aux | 85 dB | 85 dB | 85 dB | 85 dB |
| | Mic | 75 dB | 75 dB | 75 dB | 75 dB |
| FUSE | T2A/250V | T2A/250V | T2A/250V | T5A/250V | T5A/250V |
| Carton dimensions | 535X375X175mm | 550X425X180mm | 550X425X180mm | 550X455X180mm | 550X455X180mm |
| Weight | 9.25kg | 11kg | 12 kg | 14 kg | 16 kg |