

Mackie HM-400 pojačalo za slušalice

Mackie HM-400 - pojačalo za slušalice

Šifra: 15469

Kategorija proizvoda: Studijska oprema i pribor

Proizvođač: MACKIE

Cena: **186,00** EUR

One stereo main input via XLR and 1/4" jacks can be mixed with a per-channel 1/4" stereo aux input. Each channel offers 2-band EQ for quick tone shaping, stereo balance or main/aux input mix control, and output level adjustments. Also on each channel are switches for muting left and/or right signals and operating in stereo or mono. 7-segment LED meters display main input and per-channel output levels.

The HM-400 ships with an IEC power cable and occupies 1 RU in a standard 19" rack.

Distribute signal to up to twelve pairs of headphones

Occupies 1 RU

One stereo main input via XLR or 1/4" jacks

One 1/4" stereo aux input per channel

One stereo main output via XLR or 1/4" jacks

Three 1/4" headphone outputs—one on the front panel and two on the rear—per channel fed by an output level control

2-band EQ per channel for quick treble and bass adjustments

Per-channel Balance knob allows control of left/right level balance or aux/main input mix

Switches on each channel for L/R mute and St/2-Ch (stereo/mono) mode

7-segment LED metering for input and each output channel

Heavy-gauge steel chassis for rugged durability

Mackie HM-400 Specs

Form Factor Rackmount

Number of Headphone Channels 4-Channel

Headphone Output Power 550 mW per Side into 47 Ohms (Max)

EQ 2-Band EQ per Channel

Display 5 x Multi-Segment LED Meter

Connectivity

Analog Audio I/O 2 x XLR 3-Pin Balanced Input (1 Stereo Pair)

2 x 1/4" TRS Balanced/Unbalanced Input (1 Stereo Pair)

1 x 1/4" TRS Unbalanced Stereo Input

4 x 1/4" TRS Unbalanced Stereo Aux Input

2 x XLR 3-Pin Balanced Output (1 Stereo Pair)

2 x 1/4" TRS Balanced Output (1 Stereo Pair)

12 x 1/4" TRS Unbalanced Headphone Output

Performance

Frequency Response 20 Hz to 20 kHz ± 1 dB

Gain/Trim Range Inputs:

-66 to +18 dBu

Maximum Input Level Line Inputs:

+15 dBu

Aux Inputs:

+20 dBu

Maximum Output Level Headphone Outputs:

+21 dBu

Impedance Headphone Outputs:

3 Ohms (Unbalanced)

Inputs:

20 Kiloohms (Balanced)

10 Kiloohms (Unbalanced)

Aux Inputs:

10 Kiloohms (Unbalanced)

THD < 0.01% (at +4 dBu, 1 kHz, Unity Gain)

Noise -66 dB

CMRR Line Inputs:

> 42 dB (1 kHz)

Power

Power Requirements AC Input

AC Input Power 100 to 120 VAC, 50 / 60 Hz

220 to 240 VAC, 50 / 60 Hz

Power Consumption 24 W

Physical

Rackmount Size 1 RU

Dimensions 19 x 8.8 x 1.8" / 483 x 224 x 46 mm

Weight 8.0 lb / 3.6 kg