

## FOCAL TWIN6 ST6 RED - aktivni studijski monitor

---

Šifra: 16631

Kategorija proizvoda: Studijski monitori

Proizvođač: Focal

**Cena: 1.699,00 EUR**

Each driver is powered by its own amplifier for a total of 190W of RMS power for a strong and distortion-free performance. The rear panel offers a standard XLR input connector, which allows you to connect virtually any professional sound system. It also has a high-pass filter, shelving EQs for low and high frequencies, and a mid-frequency EQ to help you dial in your best sound. The focus mode provides two monitor signatures in one; 2-way monitor and 1-way full-range monitor from the woofers alone. The monitor is magnetically shielded for safe use near video monitors and other electronic equipment.

Beryllium inverted dome tweeter: exceptionally low directionality, excellent linearity and dynamics

Optimized baffle tweeter: excellent dispersion control

Composite sandwich W-cone: sound neutrality, no distortion

Focus mode: two monitors in one; 2-way monitor and 1-way full-range monitor (woofer alone)

Large laminar port: no port noises or distortion

Automatic standby mode for saving power

Settings: LF shelving, HF shelving, LPF at 160 Hz

### Focal Dual Specs

Studio Monitor

Monitor Type Active 2-Way

Enclosure Bass-Reflex, Shielded

Power Rating 190 W RMS

Drivers HF Driver: 1 x 1.5" / 3.8 cm Beryllium Inverted Dome Tweeter

LF Driver: 2 x 6.5" / 16.5 cm Composite Cone

Amplification 1 x HF Amplifier: Rated at 50 W RMS

2 x LF Amplifier: Rated at 70 W RMS

### Performance

Frequency Response 45 Hz to 40 kHz  $\pm$  3 dB

Maximum Sound Pressure Level (SPL) 112 dB

Analog Input Sensitivity/Gain +4 dBu / -10 dBV (Fixed)

Phase Adjustment None

Protections and Limiting Fuse

### Signal Processing

EQ 1 x Low-Mid Shelf: -3 to +3 dB at 250 Hz (Continuously Variable dB Increments)

1 x Mid Notch/Peak: -3 to +3 dB at 160 Hz (Continuously Variable dB Increments)

1 x HF Shelf: -3 to +3 dB at 4.5 kHz (Continuously Variable dB Increments)

Filters 1 x High-Pass at 45 to 90 Hz

Parametric EQ None

### Connectivity

Audio I/O 1 x XLR Balanced Analog Input (10 Kilohms)

### Power

AC Input Power 100 to 240 VAC, 50/60 Hz

General

Enclosure Material MDF

Dimensions (W x H x D) 20.2 x 10.2 x 13.5" / 51.4 x 25.8 x 34.4 cm

Weight 48.5 lb / 22.0 kg

Packaging Info

Package Weight 53 lb

Box Dimensions (LxWxH) 26.38 x 19.75 x 17"