

MACKIE EM-89D - dinamički vokalni mikrofon

Šifra: 15484
Kategorija proizvoda: Dinamički
Proizvođač: MACKIE

Cena: 51,00 EUR

Microphone
Form Factor Handheld / Stand/Boom Mount
Sound Field Mono
Operating Principle Pressure Gradient
Capsule 1 x Dynamic
Polar Pattern Cardioid
Orientation End Address
Circuitry Solid-State
Pad None
High-Pass Filter None
Tone Adjustment None
Indicators None
On-Board Controls None
Windscreen Built-In
Performance
Frequency Range 50 Hz to 16 kHz
Impedance 600 Ohms \pm 30% at 1 kHz
Sensitivity -52 dBV/Pa at 1 kHz
Connectivity
Output Connectors (Analog) 1 x XLR 3-Pin Male (on Mic)
Headphone Connector None
Number of Conductors 2
Power
Operating Voltage Not Specified by Manufacturer
Physical
Color Black
Mounting Mic Clip/Stand Adapter (Included)
Dimensions \varnothing : 2 x L: 7.3" / \varnothing : 5.08 x L: 18.54 cm
Weight 0.66 lb / 0.3 kg

MACKIE EM-89D, dinamički vokalni mikrofon The EM-89D utilizes a cardioid polar pattern, which rejects sound behind the mic to reduce the pickup of stage bleed and allow higher gain before feedback. The mic's dynamic moving-coil design requires no batteries or phantom power, and the balanced 3-pin XLR output ensures proper connectivity with stage boxes, mixers, and portable PA systems. The EM-89D includes a mic clip, an XLR cable, and a zipper pouch.

Mackie EM-89D Specs