**logo**e not found or type unknown

Firma: Player doo

Adresa: Cvijete Zuzorić 7 Telefon: 097 714 8673

Fax:

PIB: 89978048220 E-mail: info@player.hr

## Sontronics STC-2 Pack Silver - studijski mikrofon

Šifra: 16099

Kategorija prozivoda: Studijski Mikrofoni

Proizvođač: SONTRONICS

Cena: 256,00 EUR

accurately reproducing your source in all its glory.

Sontronics STC+2 Pack Silver - studijski mikrof

available with must-have accesssories – shockmount, nylon-mesh popshield, XLR cable and zip-up pouch – this large-diaphragm condenser mic has a fixed cardioid pattern and is ideally suited to vocals, voiceover and acoustic instruments, from acoustic guitar and piano to brass, woodwind and strings, but can also be used in pairs for all kinds of stereo applications.

STC-2's evenly balanced frequency response results in rich, defined lows and a detailed, open top end,

Like all our condenser mics, STC-2 features our signature smooth high-frequency roll-off, ensuring a natural top end and a recording that sits perfectly in the mix.

Even though STC-2 is one of our most affordable and accessible microphones, it is crafted with great care and attention to detail, both in its internal electronics and its external build.

Adding to its versatility, the STC-2 features a two-stage filter switch, giving you complete control over the low end, and a two-stage pad switch, allowing it to cope with powerful sources such as brass, drums and guitar amps.

Available in brushed silver or sleek satin black, STC-2 is supplied with its spider-style shockmount in an aluminium flightcase, for protection between sessions or out on the road.

This stunning studio tool will truly change the way you hear things!

Our STC-2 PACK is a great all-rounder for all kinds of voices and acoustic instruments, whether in the studio or in a home environment.

It's a favourite with singer/songwriters thanks to its ability to capture vocals and guitar at the same time.

POLAR PATTERN		
Cardioid		
20Hz to 20kHz		
PAD		
0dB, -10dB		

MIC TYPE

condenser

Large-diaphragm

SENSITIVITY				
-34dB ±2dB				
CONNECTOR				
3-pin XLR				
POWER				
Phantom power 48V (±4V) required				

FILTER

Linear, 75Hz

