

## SVS Prime Bookshelf Pair Black Gloss - HiFi zvučnici

---

Šifra: 18107  
Kategorija proizvoda: Hi Fi Zvučnici  
Proizvođač: SVS

Cena: **789,00** EUR

### Frequency Response / Acoustic Data:

Rated bandwidth: 48 Hz-25 kHz ( $\pm 3$  dB)

Nominal impedance: 8 ohms.

Sensitivity: 87 dB (2.83V @ 1 meter full-space, 300-3kHz)

Recommended amplifier power: 20-150 watts.

SVS Prime Bookshelf Pair Black Gloss - HiFi zvučnici

## Speaker Specs:

Bookshelf Loudspeaker

Black ash and piano gloss black finish options

Single set of 5-way binding posts

1.7" wide-flared rear-firing port

Cloth grille with pin/cup retention system

Elastomer stick-on bumper feet (adds 3mm to height)

Cabinet Dimensions: 13.2" (H) X 8" (W) X 9.4" (D)

Overall Dimensions: 13.3" (H) X 8" (W) X 10.3" (D)  
(includes grille and bumper feet)

Shipped Dimensions-2 Pack: 17.6" (H) X 22.4" (W) X  
14.4" (D)

Weight: 15.5 pounds

Shipped Weight-2 Pack: 34.7 pounds

## Driver Specs:

### 1" Aluminum Dome Tweeter:

FEA-optimized diffuser for airy and unveiled  
presentation

Aluminum dome for exceptional transient response

### 6.5" Woofers:

Long stroke motor and suspension for high output  
Polypropylene cone for excellent stiffness/mass ratio  
and pistonic behavior

Aluminum shorting ring to reduce gap inductance,  
lower distortion, and enhance high frequency response

Cast ABS-fiberglass composite basket ensures  
precision component alignment and excellent thermal  
transfer

Vented voice coil former minimizes air compression  
artifacts

## Crossover & Cabinet Specs:

### Crossover:

2-way crossover with premium-grade capacitors, air-

core inductors and heavy-trace printed circuit boards

Crossover network delivers outstanding phase coherency and time domain behavior

Tweeter-to-woofer crossover: 2.3 kHz (12 dB/octave slopes)

## **Cabinet:**

Acoustically transparent and FEA optimized grilles minimize diffraction

FEA-optimized cabinet and bracing eliminates resonances

Chamfered front baffle and flush-mounted drivers reduce edge diffraction and improved on-axis high frequency response