

MARTIN WISMAN MA 2600 - pojačalo za razglas

## MARTIN WISMAN MA 2600 - pojačalo za razglas

Šifra: 5090

Kategorija proizvoda: Pojačala

Proizvođač: Martin Wisman

Cena: **819,00** EUR

### MA 2600

#### Power Amplifier

The MA Series professional power amplifiers offer Martin Wisman renowned integrity and can handle exceptionally high power ratings in a compact, light weight 2RU package. The  $\alpha$  Series amps also feature Automatic Clip Limiting to protect connected drivers; Impedance sensing to accommodate varying impedance outputs; tunnel cooled, high efficiency heat sinks; and variable speed DC fans to limit the operating temperature and extend amplifier life. Models in the series include the MA 2600 and MA 3200.

#### Minimum Guaranteed Power

1 kHz with 0.5% THD

|                                 |       |
|---------------------------------|-------|
| <b>Stereo, 4 ohms (per ch.)</b> | 1280W |
| <b>Stereo, 8 ohms (per ch.)</b> | 800W  |
| <b>Bridge mono, 8 ohms</b>      | 2400W |

#### Performance

|   |                    |
|---|--------------------|
|   |                    |
| <b>Sensitivity</b> (volts RMS) for full rated power at 8 ohms | 0.775V, 32dB, 26dB |
| <b>Frequency Response</b><br>(at 1 watt, 20Hz - 25 kHz)       | +0dB, -0.5dB       |
| <b>Phase Response</b><br>(at 1 watt, 20Hz to 20 kHz)          | +10°, -20°         |

#### Signal to Noise Ratio below rated power

|   |                                      |
|---|--------------------------------------|
| <b>Total Harmonic Distortion (THD)</b><br>at 1 full bandwidth power, from 20 Hz to 20 kHz               |                                      |
| <b>Intermodulation Distortion (IMD)</b> 60 Hz<br>and 7 kHz at 4:1,<br>from full rated output to -35 dBt |                                      |
| <b>Damping Factor</b> (8 ohm): 20 Hz to 400 Hz  |                                      |
| <b>Low Cut:</b> Linkwitz-Riley<br>(24dB/Octave)   | Off/35Hz/80Hz                        |
| <b>Low Pass:</b> Linkwitz-Riley<br>(24dB/Octave)  | Off/80Hz/125Hz                       |
| <b>Crosstalk</b><br>(below rated power, 20 Hz to 20 kHz)  |                                      |
| <b>Common Mode Rejection</b><br>(CMR)(20 Hz to 1 kHz)   |                                      |
| <b>DC Output Offset</b> (Shorted input)   |                                      |
| <b>Input Impedance</b><br>(nominally balanced, nominally unbalanced)                                    | 20 kilohms, 10 kilohms               |
| <b>Voltage Gain</b><br>(at maximum level setting)   | 40.3dB gain at 0.775volt sensitivity |
| <b>Load Impedance</b><br>(Note: Safe with all types of loads)   | Stereo Bridge 4-8 ohms               |
|   | Mono 8 ohms                          |
| <b>AC Line Voltage and Frequency Configurations</b><br>Available ( $\pm 10\%$ )                         | ~220-240 V and 50/60 Hz              |
| <b>AC Line Current</b><br>(both amplifiers draw no more than 90 watts at idle)                          | 12A                                  |

## Construction

|                        |   |
|------------------------|---|
| <b>Ventilation</b>     | Flow-through ventilation from front to back |
| <b>Cooling</b>         | Proportional speed fan                      |
| <b>Dimensions</b>      | H x W x D: 89mmx483mmx462mm                 |
| <b>Net Weight</b>      | 18kg  |
| <b>Shipping Weight</b> | 21kg  |

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.