

MARTIN WISMAN MA 2600 - pojačalo za razglas

## MARTIN WISMAN MA 2600 - pojačalo za razglas

Šifra: 5090

Kategorija proizvoda: Pojačala

Proizvođač: Martin Wisman

Cena: **819,00** EUR

### MA 2600

#### Power Amplifier

The MA Series professional power amplifiers offer Martin Wisman renowned integrity and can handle exceptionally high power ratings in a compact, light weight 2RU package. The  $\alpha$  Series amps also feature Automatic Clip Limiting to protect connected drivers; Impedance sensing to accommodate varying impedance outputs; tunnel cooled, high efficiency heat sinks; and variable speed DC fans to limit the operating temperature and extend amplifier life. Models in the series include the MA 2600 and MA 3200.

#### Minimum Guaranteed Power

1 kHz with 0.5% THD

<b>Stereo, 4 ohms (per ch.)</b>	1280W
<b>Stereo, 8 ohms (per ch.)</b>	800W
<b>Bridge mono, 8 ohms</b>	2400W

#### Performance

<b>Sensitivity</b> (volts RMS) for full rated power at 8 ohms	0.775V, 32dB, 26dB
<b>Frequency Response</b> (at 1 watt, 20Hz - 25 kHz)	+0dB, -0.5dB
<b>Phase Response</b> (at 1 watt, 20Hz to 20 kHz)	+10°, -20°

#### Signal to Noise Ratio below rated power

<b>Total Harmonic Distortion (THD)</b> at 1 full bandwidth power, from 20 Hz to 20 kHz	
<b>Intermodulation Distortion (IMD)</b> 60 Hz and 7 kHz at 4:1, from full rated output to -35 dBt	
<b>Damping Factor</b> (8 ohm): 20 Hz to 400 Hz	
<b>Low Cut:</b> Linkwitz-Riley (24dB/Octave)	Off/35Hz/80Hz
<b>Low Pass:</b> Linkwitz-Riley (24dB/Octave)	Off/80Hz/125Hz
<b>Crosstalk</b> (below rated power, 20 Hz to 20 kHz)	
<b>Common Mode Rejection</b> (CMR)(20 Hz to 1 kHz)	
<b>DC Output Offset</b> (Shorted input)	
<b>Input Impedance</b> (nominally balanced, nominally unbalanced)	20 kilohms, 10 kilohms
<b>Voltage Gain</b> (at maximum level setting)	40.3dB gain at 0.775volt sensitivity
<b>Load Impedance</b> (Note: Safe with all types of loads)	Stereo Bridge 4-8 ohms
	Mono 8 ohms
<b>AC Line Voltage and Frequency Configurations</b> Available ( $\pm 10\%$ )	~220-240 V and 50/60 Hz
<b>AC Line Current</b> (both amplifiers draw no more than 90 watts at idle)	12A

## Construction

<b>Ventilation</b>	Flow-through ventilation from front to back
<b>Cooling</b>	Proportional speed fan
<b>Dimensions</b>	H x W x D: 89mmx483mmx462mm
<b>Net Weight</b>	18kg
<b>Shipping Weight</b>	21kg

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.