

NEUTRIK NAC3FCB

Šifra: 6035

Kategorija proizvoda: Konektori

Proizvođač: Neutrik

Cena: **10,00** EUR

Lockable cable connector, power-out, screw terminals, grey

The powerCON is a locking 3 conductor equipment AC connector with contacts for line, neutral and pre-mating ground contact. It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed in order to guarantee a safe power connection.

Attention: The powerCON is a connector without breaking capacity, i.e. the powerCON should not be connected or disconnected under load or live!

Product

Title

NAC3FCB

Gender

female

Electrical

Contact resistance

≤ 3 mΩ (inner)

Dielectric strength

4 kVdc / 2.8 kVac

Insulation resistance

> 0.1 GΩ (after damp heat test IEC 68-2-30)

Number of electrical contacts

2 + PE

Rated current per contact

20 A rms

Rated voltage

250 V ac

Mechanical

Cable O.D.

6 - 15 mm (1)

Lifetime

> 1000 mating cycles

Wiresize

2,5 mm²

Wiresize

14 AWG

Locking device

Quick Lock

(1)

Cable O.D. range limited to 6 mm - 14 mm acc. VDE

Material

Contact plating

4 μm Ag

Contacts

Bronze (CuSn6)

Insert

Polyamide (PA 6 30 % GR)

Locking element

Zinc diecast (ZnAl4Cu1)

Shell

Polyamide (PA 6 30 % GR)

Strain relief

Polyacetal (POM)

Environmental

Temperature range

-30 °C to +80 °C

Product specific

Coding

B-type for power outlet (color coding gray)

Features & Benefits

Locking 20 A / 250 V ac appliance coupler

3 contacts for line, neutral and pre-mating safety ground
Fast and easy twist lock latching system

Power
differ

Ergonomic design

User r

Unique Neutrik chuck type strain relief

UL, c

Branded with unique hologram - guarantees genuine
and authentic Neutrik product

VDE c
SEV a