

NEUTRIK NL4MP- četveropolni ugradbeni speakon konektor

Šifra: 1263

Kategorija proizvoda: Konektori

Proizvođač: Neutrik

Cena: **4,00** EUR

Neutrik // NL4MP - Speakon Chassis Connectors

4 pole chassis connector, black D-size flange, countersunk thru holes, 3/16" flat tabs

The state-of-the-art chassis connector for loudspeaker / amplifier applications. They feature a unique locking system, robust plastic housing and high current silver plated contacts.

Features & Benefits

Standard current rating 30 Amp

Glass reinforced materials make it extremely robust and dependable

Accurate twist lock latching system

Airtight design - optimized for speaker applications

Precise keyway for secure mating

Metal insert in locking area

Image not found or type unknown



Product

Connector Type

Speakon

Gender

male

Electrical

Contact resistance

≤ 3 mΩ (after lifetime)

Dielectric strength

4 kVdc (peak)

Insulation resistance

> 1 GΩ (after dampheat)

Rated current per contact

30 A rms continuous

Rated current per contact

40 A audiosignal, duty cycle 50 %

Rated voltage

250 V (Insulation)

Attention

speakON is NOT to be used as an AC mains connector!

Mechanical

Lifetime

> 5000 mating cycles

Wiring

flat tabs for 3/16" (FASTON® 4.8 x 0.5 mm) or soldering

Locking device

Quick Lock

Mounting direction

front & rear

Chassis shape

D

Layout

standard hole position, thru holes

Material

Contact plating

4 μm Ag

Contacts

Bronze (CuSn6)

Shell

Polyamide (PA 6 30 % GR) black

Environmental

Approvals

UL,CSA

Flammability

UL 94 HB

Solderability

Complies with IEC 68-2-20

Temperature range

-30 °C to +80 °C

