

RELOOP RP-7000 MK2 - DJ gramofon

RELOOP RP-7000 MK2 - DJ gramofon

Šifra: 12095

Kategorija proizvoda: DJ gramofoni

Proizvođač: Reeloo

Cena: **525,00** EUR

Napomena: Uz gramofon se ne dobija igla!

FEATURES

New features of the MK2 version:

Built for the club: rigid chassis construction with an even heavier design with additional reinforcements made of metal, rubber and moulding compound for high vibration damping and isolation

More powerful starting torque (adjustable from 2.8 - 4.5 kg/cm)

Fine-tuned motor control for further optimization of wow and flutter and rotation

Newly developed, height-adjustable tone arm base (VTA) and anti-skating control

Particularly lightweight and rigid satin aluminium material used for tone arm

Adjustable pitch scale for precise adjustments

Optional ground terminal offers additional protection in complex club & studio environments

Easily replaceable, freely rotatable LED needle illumination in new unibody aluminium design

High-quality and hard-wearing deep black, metallic finish

Quartz driven DJ turntable with upper-torque direct drive

Adjustable brake speed (0.2 - 6 sec.)

Precise control of motor with 3 speeds (33 1/3, 45 & 78 rpm)

Precision-manufactured, die cast aluminium turntable

Rubber inlays for reduction of vibrations and background noise

Statically balanced universal S-shaped tone arm with hydraulic lift and anti-skating mechanism

Universal connection for pick-up systems (SME)
Pitch range +/-8 %, +/-16 %, +/-50 % (ultra pitch)
Quartz lock
Additional start/stop button for vertical positioning
Reverse function: switch for forward and reverse playback
Recessed connection cavity for easy flight-case installation & seamless adjustment
Phono and line out (no grounding required)
Removable mains and RCA cables
Safety mains switch
Shock-absorbing feet against vibrations
Incl. turntable, slipmat, LED needle light, counterweight, phono RCA cable with grounding, power cord, operating instructions, without cartridge

TECHNICAL DATA

Turntable:

Type: direct-drive turntable
Drive: quartz driven upper-torque direct drive
Motor: 16-pole, 3-phase, brushless motor
Turntable speeds: 3 speeds, manual (33 1/3, 45, 78 RPM)
Starting torque: 2.8 - 4.5 kg/cm (adjustable)
Adjustable stop time (0.2 - 6 sec.)
Start-up time / change to RPM: <0.2 sec
Wow and flutter: 0.01% WRMS*
S/N ratio: > 55dB (DIN-B)
Brake system: electronic brake
Record weight: recommended 800g

Platter:

Material: die cast aluminium
Diameter: 332 mm
Weight: approx. 1.5 kg

Tone arm:

Type: universal, static balanced, S-shaped
Effective length: 230 mm
Overhang: 15 mm
Tracking error range: < 3°
Offset Angle: 22°
Stylus Pressure: 0 - 4 g
VTA setting range: 0-6 mm
Useable weight of pick-ups: 3.5~8.5 g (incl. headshell 13~18 g)
Anti-skating range: 0 - 3 g
Effective tone arm mass: 12.8 g (incl. Reloop Headshell ~10 g)

Connections:

1x Phono/Line Out (gold-plated), 1x GND earth connection

General:

Power supply: AC 115/230 V, 60/50 Hz (EU/US), AC 100 V, 50/60 Hz (JP)

Power consumption: 13 W

Dimensions: 458 x 144.6 x 354 mm

Weight: approx. 11.7 kg